

DESCRIPTION

- Used to repair capillary cracks and honeycombs that occur during concrete polishing applications.

INTENDED USES

- Used in the polishing of concrete floors.

PROPERTIES

- Reduces the consumption of liquid surface hardener.
- Provides high strength
- Provides adhesion on the surface.
- Contributes to polishing applications.

APPLICATION

- After grinding, **PORE SEALER** is applied to the surface by either by spraying or pouring.
- It is applied intensively to the parts that need to be repaired with a mop or squeegee.
- With the dust that will emerge during the wiping process, **PORE SEALER** will become a mortar and fill the pores and capillary cracks.
- Depending on the condition of the concrete, 70 or 120 grit diamonds should be used for the grinding process.
- After curing for 24 hours, the next grinding steps can be initiated.

SHELF LIFE

- The shelf life of an unopened package stored in a dry, cool place is 12 months from the date of manufacture.

TECHNICAL DATA

Color	: White liquid
Application temperature	: (+5°C)-(+35°C)
pH	: 9±1,5
Consistency	: 1,01±0,03 kg/L
Time required to continue grinding	: 24 hours

- These values are obtained under laboratory conditions ((23±2) °C temperature, 50% relative humidity) and may differ due to worksite conditions.
- MYFIX YILDIZ YAPI KİMYASALLARI SANAYİ VE TİCARET LİMİTED ŞİRKETİ is not responsible for the application errors that may arise if the application conditions and precautions outlined above are not followed for the purpose of the product.

WARNINGS AND RECOMMENDATIONS

- The application must be done according to standards and instructions.
- The application surface should be left as a final coating
- After application, hands and applications tools should be thoroughly washed with water.
- The indicated consumption amount is general information and may differ due to application conditions and surface features.
- The application must be done by our expert implementing dealer.
- The responsibility of the applications not performed by our expert implementing dealers belongs to the company that implements them.

CONSUMPTION

- 0.1 L/m² (Consumption can be increased depending on honeycomb intensity and size)

PACKAGING

- 30 L Jerry Can and 1000L IBC