

DEKOR LINE PATTERN MINERAL EXTERIOR PLASTER

DESCRIPTION

- White cement based, high adhesion strength with special polymer reinforcement, line textured plaster provides a decorative finish.

INTENDED USES

- Interior and Exterior applications,
- Used as a decorative plaster on thermal insulation systems on exterior walls.

PROPERTIES

- Easy to apply.
- Has high abrasion resistance against external factors.
- Creates a natural and decorative texture on surface due to special filling size.
- Allows the structure to breathe.
- Has high water vapour permeability.
- Resistant to freeze-thaw cycle.
- Has high water repellent.
- Does not lead to cracks & shrinkages.
- Paint can be applied on it.

SURFACE TREATMENT

- The application board surface must be clean and dry.
- The surface should be free from residues that will prevent adhesion.
- Apply **DSA Decorative Plaster Primer** with a brush or roller before application.

APPLICATION

- Slowly pour 25 kg **DEKOR LINE PATTERN** powder into 4.5-5.0lt water and thoroughly mix it with a low-speed mixer until it becomes a smooth, homogeneous substance. Do not add any additional additives, unless mentioned in the instructions.
- Rest the prepared mortar for 10 minutes and stir it again for 1-2 minutes before application.
- Apply **DEKOR LINE PATTERN** to surface with a steel trowel evenly.
- Complete patterns by making circular movements with a plastic trowel, 5 minutes after applying mortar homogeneously.
- Trowel should be cleaned frequently during patterning.
- Surface can be painted with exterior paint if required.
- Make sure that the mortar has completely set before proceeding to painting application.

WARNINGS AND RECOMMENDATIONS

- Do not apply to horizontal and inclined surfaces.
- Do not apply directly on bricks or aerated concretes.
- DSA Decorative Plaster Primer should be used to get better adhesion strength and better performance from the product.
- Do not breathe the powder or contact with skin or eyes as it is cement-based.
- After application, hands and applications tools should be thoroughly washed with water.
- The indicated consumption amount is general information and may differ due to application conditions

TECHNICAL DATA

Appearance	White powder
Application temperature	(+5°C) - (+30°C)
Temperature resistance	(-30°C) - (+60°C)
Application thickness	~ 3 mm
Adhesion strength through pull-off test	0.8 N/mm ²
Dry film thickness	E5
Grain size	S4
Water vapour transmission rate	V0
Water transmission rate	W2
Crack covering feature	A0
Carbon dioxide permeability	C0

- These values are obtained under laboratory conditions ((23±2) °C temperature, 50% relative humidity) and may differ due to worksite conditions.
- MYFIX YILDIZ YAPI KİMYASALLARI SANAYİ VE TİCARET LİMİTED ŞİRKETİ is not responsible for the application errors that may arise if the application conditions and precautions outlined above are not followed for the purpose of the product.

CONSUMPTION

- 2.5-3.0 kg/m²

COMPLEMENTARY PRODUCT(S)

- DSA Decorative plaster primer

PACKAGING

- 25 kg Kraft paper bag (pallet 64 bags, 1600 kg)

SHELF LIFE

- Shelf life of an unopened package stored in a dry, cool place is 12 months from the date of manufacture.

QUALITY CERTIFICATES

- In Accordance with **TS 7847** standards.
- Class: **E5-S4-V0-W2-A0-C0**.

<h1>G</h1>	
YILDIZ YAPI KİMYASALLARI SAN. ve TİC. LTD. ŞTİ. İstanbul Mermerçiler Küçük San. Sit. 18. Cad. No: 22 Köşeler Köyü - Dilovası / KOCAELİ	
13	
TS 7847/JUNE 2012 DEKOR LINE PATTERN	
Dry film thickness	: E5
Grain size	: S3
Water vapour transmission rate	: V0
Water transmission rate	: W0
Crack covering feature	: A0
Carbon dioxide permeability	: C0