

DEKOR 1.2 mm

MINERAL EXTERIOR PLASTER



DESCRIPTION

- Cement based plaster with high adhesion strength and decorative finish.

INTENDED USES

- Interior and Exterior applications,
- Used as a decorative plaster on thermal insulation systems on exterior walls.

PROPERTIES

- Easy to apply.
- Has high abrasion resistance against external factors.
- Creates a natural and decorative texture on surface due to special filling size.
- Allows the structure to breathe.
- Does not lead to cracks & shrinkages.
- Paint can be applied on it.

SURFACE TREATMENT

- The application board surface must be clean and dry.
- The surface should be free from residues that will prevent adhesion.
- Apply **DSA Decorative Plaster Primer** with a brush or roller before application.

APPLICATION

- The application should be planned to be completed at one time.
- Desired pattern is given to the surface with a plastic trowel before **DEKOR** dries.
- After **DEKOR** is completely set, flexible exterior coating of the preferred colour is applied on it.
- Slowly pour 25 kg **DEKOR** powder into 5.5-6.0lt water and thoroughly mix it with a low-speed mixer until it becomes a smooth, homogeneous substance. Do not add any additional additives, unless mentioned in the instructions.
- Rest the prepared plaster for 10 minutes and stir it again for 1-2 minutes before application.
- Apply **DEKOR** to surface with a steel trowel evenly.
- Complete patterns by making circular movements with a plastic trowel, 5 minutes after applying mortar homogeneously.
- Trowel should be cleaned frequently during patterning.
- Surface can be painted with exterior paint if required.
- Make sure that the plaster has completely set before proceeding to painting application.

WARNINGS AND RECOMMENDATIONS

- Do not apply on horizontal and inclined surfaces.
- Do not apply directly on bricks or gas concrete.
- **DSA Decorative plaster primer** should be used to get better adhesion strength and better performance from the product.
- Do not breathe the powder or contact with skin or eyes as it is cement-based.
- After application, hands and applications tools should be thoroughly washed with water.
- The indicated consumption amount is general information and may differ due to application conditions and surface features.

TECHNICAL DATA

| | |
|--------------------------------|-------------------|
| Appearance | White powder |
| Application Temperature | (+5°C) - (+30°C) |
| Temperature Resistance | (-30°C) - (+60°C) |
| Application Thickness | ~1,2 mm |
| Dry film thickness | E5 |
| Grain size | S3 |
| Water vapour transmission rate | V0 |
| Water transmission rate | W0 |
| Crack covering feature | A0 |
| Carbon dioxide permeability | C0 |

- These values are obtained under laboratory conditions ((23±2) °C temperature, 50% relative humidity) and may differ due to worksite conditions.
- **MYFIX YILDIZ YAPI KİMYASALLARI SANAYİ VE TİCARET LİMİTED ŞİRKETİ** is not responsible for the application errors that may arise if the application conditions and precautions outlined above are not followed for the purpose of the product.

COMPLEMENTARY PRODUCT(S)

- **DSA Decorative plaster primer**

CONSUMPTION

- 2.5-3.0 kg/m² (For 3 mm application)

PACKAGING

- 25 kg Kraft bag (Pallet 64 bags, 1600 kg)

SHELF LIFE

- Shelf life of an unopened package stored in a dry, cool place is 12 months from the date of manufacture.

QUALITY CERTIFICATES

- In Accordance with **TS 7847** standards.
- Class: **E5-S3-V0-W0-A0-C0**.

| | |
|--|------|
| G | |
| YILDIZ YAPI KİMYASALLARI SAN. ve TİC. LTD. ŞTİ. İstanbul Mermerçiler Küçük San. Sit. 18. Cad. No: 22 Köşeler Köyü - Dilovası / KOCAELİ | |
| 13 | |
| 070645-TSE-03/02 TS 7847/JUNE 2012 DEKOR | |
| Dry film thickness | : E5 |
| Grain size | : S3 |
| Water vapour transmission rate | : V0 |
| Water transmission rate | : W0 |
| Crack covering feature | : A0 |
| Carbon dioxide permeability | : C0 |

Yıldız Yapı Kimyasalları San. ve Tic. Ltd. Şti.

KOCAELİ KOBİ Organize Sanayi Bölgesi 18. Cadde No: 22 Köşeler - Dilovası / KOCAELİ / TURKEY

+90 (216) 469 66 33 +90 (262) 728 11 10 | www.myfixyapikim.com | © f d in myfixyapikimyasallari