



DECLARATION OF PERFORMANCE (NO: 05.PB 12004.004)
EU Construction Products Directive Annex 3 (305/2011/EU)

1. Unique identification code of the product-type: **MYFIX MYİSTANBUL Flex Ceramic Tile Adhesive**
2. Type, batch or serial number or any other elements allowing identification of the building material (in accordance with the fourth paragraph of Article 13 of the Regulation): **Cementitious (C) - Standard performance (1)- Reduced slip feature (T) - Extended open time (E) – Deformable (S1)
C1TES1**
3. Intended use or uses of the building material, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: **EN 12004:2017**
4. The name of the manufacturer, registered trade name or trademark and contact address of the manufacturer (in accordance with the fifth paragraph of Article 13 of the Regulation): **YILDIZ YAPI KİMYASALLARI SAN. ve TİC. LTD. ŞTİ.
İstanbul Mermerciler Küçük Sanayi Sitesi 18. Cad.
No:22 Dilovası / KOCAELİ / TURKEY**
5. Where applicable, name and address of the authorised representative (whose mandate covers the task specified in the second paragraph of Article 14 of the Regulation): **Not relevant**
6. System or systems of assessment and verification of the stability of the performance of the building material (as specified in Annex-5 of the Regulation): **System 3**
7. In a declaration of performance (DOP) for a building material covered by a harmonized standard: Organized by **TSE** by applying **manufacturer's factory production control** under **System 3**, one of the systems of evaluation and verification of performance invariance, **determination of material type based on type test of approved laboratory material, type calculations, values given in table or explanatory documents.**
8. European Technical Assessment References: **Not relevant**
9. Declared performance:

| Essential characteristics | Performance | Harmonised Technical Specifications |
|---|---|-------------------------------------|
| Initial tensile adhesion strength | ≥ 0.5 N/mm ² | EN 12004-2:2017 Article 8.3 |
| Tensile adhesion strength after water cycle | ≥ 0.5 N/mm ² | EN 12004-2:2017 Article 8.3 |
| Tensile adhesion strength after heat cycle | ≥ 0.5 N/mm ² | EN 12004-2:2017 Article 8.3 |
| Tensile adhesion strength after freeze/thaw cycling | ≥ 0.5 N/mm ² | EN 12004-2:2017 Article 8.3 |
| Extended Open Time: Tensile adhesion strength | After 30 minutes ≥ 0.5 N/mm ² | EN 12004-2:2017 Article 8.1 |
| Slip | ≤ 0.5 mm | EN 12004-2:2017 Article 8.2 |
| Deformability | 2.5 mm ≤ S1 < 5 mm | EN 12004-2:2017 Article 8.6 |
| Fire response class | A1 | EN 13501-1 |

*Our products do not contain hazardous substances for health and the environment.

10. The building material described in the first and second paragraphs has the performance declared in paragraph 9 of this Annex. The entire liability for this performance statement belongs solely to the manufacturer as defined in the fourth paragraph of this Annex.

Signed on behalf of the manufacturer:

Uğur YILDIZ / General Manager

TURKEY / 23.11.2021