

DECLARATION OF PERFORMANCE (NO: 03.PB 1504-2.003, 2163-CPR-0560-1) EU Construction Products Directive Annex 3 (305/2011/EU)

- Unique identification code of the product-type:
 Type, batch or serial number or any other elements allowing identification of the building material (in accordance with the fourth paragraph of Article 13 of the Regulation):
- 3. Intended use or uses of the building material, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:
- 4. The name of the manufacturer, registered trade name or trademark and contact address of the manufacturer (in accordance with the fifth paragraph of Article 13 of the Regulation):
- 5. Where applicable, name and address of the authorised representative (whose mandate covers the task specified in the second paragraph of Article 14 of the Regulation):
- System or systems of assessment and verification of the stability of the performance of the building material (as specified in Annex-5 of the Regulation):

MYFIX DSA Decorative plaster primer

Principle 1: Protection against foreign material (PI)

Method 1.2: Impregnation application (I)

EN 1504-2:2005

YILDIZ YAPI KİMYASALLARI SAN. ve TİC. LTD. ŞTİ.

İstanbul Mermerciler Küçük Sanayi Sitesi 18. Cad. No:22 Dilovası / KOCAELİ / TURKEY

Not relevant

System 2+

7. In a declaration of performance (DOP) for a building material covered by a harmonized standard: <u>UNIVERSAL</u> <u>CERTIFICATION and identification number 2163</u> are used for the evaluation and verification of the performance of the system under <u>the control of the factory production</u> under <u>System 2+</u> and <u>the continuous monitoring,</u> <u>measurement and evaluation of the initial inspection and the factory production control of the production</u> <u>facility, the performance consistency certificate, factory production conformity certificate/test</u>.

8. European Technical Assessment References:

lot relevant
lot relevant

9. Declared performance:

Essential characteristics	Performance	Harmonised Technical Specifications
Capillary water absorption and water permeability	W < 0.1 kg/m ² .h ^{0.5}	EN 1062-3
Processing depth	Class I: < 10 mm	EN 14630
Fire response class	A1 (Amount of organic matter <1%)	EN 13501-1
* Our products do not contain hazardous substances for health and the environment.		

10. The building material described in the first and second paragraphs has the performance declared in paragraph 9 of this Annex. The entre liability for this performance statement belongs solely to the manufacturer as defined in the fourth paragraph of this Annex.

Signed on behalf of the manufacturer:

Uğur YILDIZ / General Manager

TURKEY / 23.11.2021