



DECLARATION OF PERFORMANCE (NO: 01.PB 998-1.004)
EU Construction Products Directive Annex 3 (305/2011/EU)

1. Unique identification code of the product-type: **MYFIX HS-530 Hand use plaster**
2. Type, batch or serial number or any other elements allowing identification of the building material (in accordance with the fourth paragraph of Article 13 of the Regulation):
Designed thick/fine plaster mortar
General purpose thick/fine plaster mortar (G)
3. Intended use or uses of the building material, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: EN 998-1:2017
4. The name of the manufacturer, registered trade name or trademark and contact address of the manufacturer (in accordance with the fifth paragraph of Article 13 of the Regulation):
YILDIZ YAPI KİMYASALLARI SAN. ve TİC. LTD. ŞTİ.
İstanbul Mermerciler Küçük Sanayi Sitesi 18. Cad.
No:22 Dilovası / KOCAELİ / TURKEY
5. Where applicable, name and address of the authorised representative (whose mandate covers the task specified in the second paragraph of Article 14 of the Regulation): Not relevant
6. System or systems of assessment and verification of the stability of the performance of the building material (as specified in Annex-5 of the Regulation): System 4
7. In a declaration of performance (DOP) for a building material covered by a harmonized standard: Factory production control and product type determination by the manufacturer
8. European Technical Assessment References: Not relevant
9. Declared performance:

| Essential characteristics | Performance | Harmonised Technical Specifications |
|---------------------------------------|---|-------------------------------------|
| Dry bulk density | 1400±300 kg/m ³ | EN 1015-10 |
| Compressive strength | CS IV; ≥ 6 N/mm ² | EN 1015-11a |
| Flexural strength | ≥0.5 N/mm ² FP(A) | EN 1015-12 |
| Capillary water absorption | W ₀ | EN 1015-18 |
| Average thermal conductivity | (λ _{10,dry}) <0.61 W/m.K P=50% | EN 1745, A.12 |
| Water vapour permeability coefficient | ≤25 μ | EN 1015-19a,b |
| Fire response class | A1 (Amount of organic matter <1%) | EN 13501-1 |

*Our products do not contain hazardous substances for health and the environment.

10. The building material described in the first and second paragraphs has the performance declared in paragraph 9 of this Annex. The entire liability for this performance statement belongs solely to the manufacturer as defined in the fourth paragraph of this Annex.

Signed on behalf of the manufacturer:

Uğur YILDIZ / General Manager

TURKEY / 22.05.2018