



DECLARATION OF PERFORMANCE (NO: 03.PB 1504-2.007, 2163-CPR-0560)
EU Construction Products Directive Annex 3 (305 / 2011 / EU)

1. Unique identification code of the product-type: **MYFIX PORE SEALER**
2. Type, batch or serial number or any other elements allowing identification of the building material (In accordance with the fourth paragraph of Article 13 of the Regulation): Principle 1: Protection against foreign material (PI)
Method 1.2: Impregnation Application (I)
3. Intended use or uses of the building material, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: EN 1504-2:2005
4. The name of the manufacturer, registered trade name or trademark and contact address of the manufacturer (in accordance with the fifth paragraph of Article 13 of the Regulation): **YILDIZ YAPI KİMYASALLARI SAN. ve TİC. LTD. ŞTİ.**
İstanbul Mermerciler Küçük Sanayi Sitesi 18. Cad.
No:22 Dilovası / KOCAELİ / TURKEY
5. Where applicable, name and address of the authorised representative (whose mandate covers the task specified in the second paragraph of Article 14 of the Regulation): Not relevant
6. System or systems of assessment and verification of constancy of performance of the building material (As stated in Annex-5 of the Regulation): System 2+
7. In a declaration of performance (DOP) for a building material covered by a harmonized standard: **UNIVERSAL CERTIFICATION and identification number 2163** are used for the evaluation and verification of the performance of the system under **the control of the factory production** under **System 2+** and **the continuous monitoring, measurement and evaluation of the initial inspection and the factory production control of the production facility, the performance consistency certificate, factory production conformity certificate/test.**
8. European Technical Assessment References: Not relevant
9. Declared performance:

Essential characteristics	Performance	Harmonised Technical Specifications
Capillary water absorption and water permeability	$W < 0.1 \text{ kg/m}^2 \cdot \text{h}^{0.5}$	EN 1062-3
Processing depth	Class I: < 10 mm	EN 14630
Fire response class	B-s1,d0 (Organic matter >%1)	EN 13501-1

10. The building material described in the first and second paragraphs has the performance declared in paragraph 9 of this Annex. The entire liability for this performance statement belongs solely to the manufacturer as defined in the fourth paragraph of this Annex.

Signed on behalf of the manufacturer:

Uğur YILDIZ / General Manager

TURKEY / 07.09.2022