

DECLARATION OF PERFORMANCE (NO: 03.PB 1504-2.020, 2163-CPR-0560-7) EU Construction Products Directive Annex 3 (305/2011/EU)

- 1. Unique identification code of the product-type:
- Type, batch or serial number or any other elements allowing identification
 of the building material (in accordance with the fourth paragraph of Article
 13 of the Regulation):
- Intended use or uses of the building material, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:
- 4. The name of the manufacturer, registered trade name or trademark and contact address of the manufacturer (in accordance with the fifth paragraph of Article 13 of the Regulation):
- 5. Where applicable, name and address of the authorised representative (whose mandate covers the task specified in the second paragraph of Article 14 of the Regulation):
- 6. System or systems of assessment and verification of the stability of the performance of the building material (as specified in Annex-5 of the Regulation):

MYFIX BB-400 Stamped concrete surface hardener

Principle 5: Physical Resistance / Surface Improvement

Method 5.1: Coating Application (C)

EN 1504-2:2005

YILDIZ YAPI KİMYASALLARI SAN. ve TİC. LTD. ŞTİ. İstanbul Mermerciler Küçük Sanayi Sitesi 18. Cad.

No:22 Dilovası / KOCAELİ / TURKEY

Not relevant

System 2+

- 7. In a declaration of performance (DOP) for a building material covered by a harmonized standard: <u>UNIVERSAL CERTIFICATION</u> and identification number 2163 are used for the evaluation and verification of the performance of the system under the control of the factory production under System 2+ and the continuous monitoring, measurement and evaluation of the initial inspection and the factory production control of the production facility, the performance consistency certificate, factory production conformity certificate/test.
- 8. European Technical Assessment References:

9. Declared performance:

Not relevant

Essential characteristics	Performance	Harmonised Technical Specifications
Abrasion resistance	≤1000 mm³	EN 13892-3
Capillary water absorption and water permeability	W<0.1 kg/m ² .h ^{0.5}	EN 1062-3
Impact resistance	Class II: ≥ 10 Nm	EN ISO 6272-1
Adhesion strength by pull-off	Without a traffic load ≥ 0.8 N/mm²	EN 1542
Fire response class	A1 (Amount of organic matter <1%)	EN 13501-1
*Our products do not contain hazardous substances fo	or health and the environment.	

10. The building material described in the first and second paragraphs has the performance declared in paragraph 9 of this Annex. The entre liability for this performance statement belongs solely to the manufacturer as defined in the fourth paragraph of this Annex.

Signed on behalf of the manufacturer:

Uğur YILDIZ / General Manager

TURKEY /12.05.2020