



**DECLARATION OF PERFORMANCE (NO: 05.PB 12004.003, 070645-TSE-05/04)**  
**EU Construction Products Directive Annex 3 (305/2011/EU)**

1. Unique identification code of the product-type: **MYFIX EXTRAFLEX Ceramic tile adhesive**
2. Type, batch or serial number or any other elements allowing identification of the building material (in accordance with the fourth paragraph of Article 13 of the Regulation): **Cementitious (C) - Standard performance (1) - Reduced slip feature (T) – Extended open time (E)  
C1TE**
3. Intended use or uses of the building material, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: **EN 12004:2017**
4. The name of the manufacturer, registered trade name or trademark and contact address of the manufacturer (in accordance with the fifth paragraph of Article 13 of the Regulation): **YILDIZ YAPI KİMYASALLARI SAN. ve TİC. LTD. ŞTİ.  
İstanbul Mermerciler Küçük Sanayi Sitesi 18. Cad.  
No:22 Dilovası / KOCAELİ / TURKEY**
5. Where applicable, name and address of the authorised representative (whose mandate covers the task specified in the second paragraph of Article 14 of the Regulation): **Not relevant**
6. System or systems of assessment and verification of the stability of the performance of the building material (as specified in Annex-5 of the Regulation): **System 3**
7. In a declaration of performance (DOP) for a building material covered by a harmonized standard: Organized by **TSE** by applying **manufacturer's factory production control** under **System 3**, one of the systems of evaluation and verification of performance invariance, **determination of material type based on type test of approved laboratory material, type calculations, values given in table or explanatory documents.**
8. European Technical Assessment References: **Not relevant**
9. Declared performance:

Essential characteristics	Performance	Harmonised Technical Specifications
Initial tensile adhesion strength	≥ 0.5 N/mm <sup>2</sup>	EN 12004-2:2017 Article 8.3
Tensile adhesion strength after water cycle	≥ 0.5 N/mm <sup>2</sup>	EN 12004-2:2017 Article 8.3
Tensile adhesion strength after heat cycle	≥ 0.5 N/mm <sup>2</sup>	EN 12004-2:2017 Article 8.3
Tensile adhesion strength after freeze/thaw cycling	≥ 0.5 N/mm <sup>2</sup>	EN 12004-2:2017 Article 8.3
Extended Open Time: Tensile adhesion strength	After 30 minutes ≥ 0.5 N/mm <sup>2</sup>	EN 12004-2:2017 Article 8.1
Slip	≤ 0.5 mm	EN 12004-2:2017 Article 8.2
Fire response class	A1	EN 13501-1

\*Our products do not contain hazardous substances for health and the environment.

10. The building material described in the first and second paragraphs has the performance declared in paragraph 9 of this Annex. The entire liability for this performance statement belongs solely to the manufacturer as defined in the fourth paragraph of this Annex.

Signed on behalf of the manufacturer:

Uğur YILDIZ / General Manager

TURKEY / 23.11.2021