

DECLARATION OF PERFORMANCE (NO: 04.PB 1504-03.003, 2163-CPR-0561-1) EU Construction Products Directive Annex 3 (305/2011/EU)

- 1. Unique identification code of the product-type:
- 2. Type, batch or serial number or any other elements allowing identification of the building material (in accordance with the fourth paragraph of Article 13 of the Regulation):
- Intended use or uses of the building material, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:
- 4. The name of the manufacturer, registered trade name or trademark and contact address of the manufacturer (in accordance with the fifth paragraph of Article 13 of the Regulation):
- 5. Where applicable, name and address of the authorised representative (whose mandate covers the task specified in the second paragraph of Article 14 of the Regulation):
- 6. System or systems of assessment and verification of the stability of the performance of the building material (as specified in Annex-5 of System 2+ the Regulation):

MYFIX REPAIR SW Waterproof structural repair mortar

Principle 3: Renovation of concrete

Method 3.1: Mortar implementation by hand

Method 3.2: Re-casting concrete

(R3)

EN 1504-3:2008

YILDIZ YAPI KİMYASALLARI SAN. ve TİC. LTD. ŞTİ.

İstanbul Mermerciler Küçük Sanayi Sitesi 18. Cad. No:22 Dilovası / KOCAELİ / TURKEY

Not relevant

7. In a declaration of performance (DOP) for a building material covered by a harmonized standard: <u>UNIVERSAL CERTIFICATION</u>
<u>and identification number 2163</u> are used for the evaluation and verification of the performance of the system under <u>the</u>
<u>control of the factory production</u> under <u>System 2+</u> and <u>the continuous monitoring, measurement and evaluation of the</u>
<u>initial inspection and the factory production control of the production facility, the performance consistency certificate,</u>
<u>factory production conformity certificate/test.</u>

8. European Technical Assessment References:

Not relevant

9. Declared performance:

Essential characteristics	Performance	Harmonised Technical Specifications
Compressive strength	Class R3; ≥25 MPa	EN 12190
Chloride ion content	≤0.05%	EN 1015-17
Bond strength formed by adhesion	≥1.5 MPa	EN 1542
Restrained shrinkage / expansion	≥1.5 MPa	EN 12617-4
Resistance to carbonation	Acceptable	EN 13295
Elasticity module	Class R3; ≥15 GPa	EN 13412
Capillary water absorption	Class R3; ≤0.5 kg/m ² .h ^{0.5}	EN 13057
Fire response class	A1 (Organic matter <%1)	EN 13501-1
*Our products do not contain hazardous substances for health and the environment.		

10. The building material described in the first and second paragraphs has the performance declared in paragraph 9 of this Annex. The entre liability for this performance statement belongs solely to the manufacturer as defined in the fourth paragraph of this Annex.

Signed on behalf of the manufacturer:

Uğur YILDIZ / General Manager

TURKEY / 23.11.2021