



DECLARATION OF PERFORMANCE (NO: 04.PB 1504-03.005, 2163-CPR-0561-1)
EU Construction Products Regulation Annex-3 (305/2011/EU)

1. Product type identification code: **MYFIX STOPPER Active water sealant**
2. Type, batch or serial number, or any other element allowing identification of the construction product as required pursuant to Article 13: Principle 3: Concrete Restoration
Method 3.1: Applying mortar by hand
3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification as foreseen by the manufacturer: EN 1504-3 :2008
4. Name, registered trade name or registered trademark, and address of the manufacturer (in accordance with the fifth paragraph of Article 13 of the Regulation): **YILDIZ YAPI KİMYASALLARI SAN. ve TİC. LTD. ŞTİ.**
İstanbul Mermeriler Küçük Sanayi Sitesi 18. Cad.
No:22 Köşeler Köyü-Dilovaşı / KOCAELİ
5. If applicable, the name and address of the authorized representative (who has the duties specified in the second paragraph of Article 14 of the Regulation): Not available
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex 5: System 2+
7. In a declaration of performance for a construction product that is within the scope of a harmonized standard: by **UNIVERSAL CERTIFICATION and ID number 2163, applying continuous surveillance, measurement, and evaluation of factory production control and initial inspection of the production plant and factory production control** under **System 2+, one of the** systems for evaluating and verifying the constancy of performance, **regarding constancy of performance certificate, factory production conformity certificate, test/reports** edited.
8. A European Technical Assessment issued on: Not available
9. Declared performance:

Essential characteristics	Performance	Harmonized Technical Specification
Compressive strength	Class R3; ≥ 25 MPa	TS EN 12190
Chloride ion content	$\leq 0.05\%$	TS EN 1015-17
bond formed by adhesion	≥ 1.5 MPa	TS EN 1542
Limited shrinkage/expansion	≥ 1.5 MPa	TS EN 12617-4
Resistance to carbonation	Passed	TS EN 13295
Elastic modulus	Class R3; ≥ 15 GPa	TS EN 13412
Capillary water absorption	Class R3; ≤ 0.5 kg/m ² .h ^{0.5}	TS EN 13057
Fire reaction class	A1 (Organic matter <1%)	TS EN 13501-1

*Our products do not contain hazardous substances for health and the environment.

10. The construction material defined in the first and second paragraphs of this Annex has the performance declared in paragraph 9 of this Annex. All responsibility for this declaration of performance rests solely with the manufacturer described in paragraph 4 of this Annex.

Signed on behalf of the manufacturer:

Uğur YILDIZ/ General Manager
KOCAELİ/ 23.11.2021