

DESCRIPTION

- Acrylic copolymer based, filled, primer used to strengthen interior and exterior surfaces.

INTENDED USES

- On gross concrete surfaces with high water absorption, on walls and ceilings,
- On cement and especially gypsum based interior and exterior plasters,
- Increases adherence before application of decorative plaster mortar on thermal insulation plaster mortars.

PROPERTIES

- Easy to use.
- Creates strong bonds between the decorative coatings in the applied areas.
- Has high adherence.
- Has high defect correction feature and white colour.

SURFACE TREATMENT

- The surface must be clean, dry, smooth and solid.
- The surface must be cleaned from residues that will prevent adhesion.

APPLICATION

- Product must be mixed before use.
- Apply it to the interior and exterior directly by brush, roller or spraying method.
- It can be thinned with water. (Max. 20%)

WARNINGS AND RECOMMENDATIONS

- After application, hands and applications tools should be thoroughly washed with water.
- During application, the surface must be protected from wind and direct sunlight.
- It is recommended to apply single layer coat 1 day before decorative coating.
- The indicated consumption amount is general information and may differ due to application conditions and surface features.

TECHNICAL DATA

Appearance	White liquid
Application temperature	(+5°C) - (+30°C)
Set time	1 hour
Completely drying time	6 hours
Density	1.50±0.04 g/ml
Adhesion strength through pull-off test	≥ 2.0 N/mm ²

- These values are obtained under laboratory conditions ((23±2) °C temperature, 50% relative humidity) and may differ due to worksite conditions.
- MYFIX YILDIZ YAPI KİMYASALLARI SANAYİ VE TİCARET LİMİTED ŞİRKETİ is not responsible for the application errors that may arise if the application conditions and precautions outlined above are not followed for the purpose of the product.

CONSUMPTION

- 0.1 kg/m² (for one layer)

PACKAGING

- 15 litre Plastic buckets

SHELF LIFE

- Shelf life of an unopened package stored in a dry, cool place is 12 months from the date of manufacture. Protect from frost.

QUALITY CERTIFICATES

- Adhesion strength through pull-off test-TSE Test report-TS EN 1504-2.

 2163	
YILDIZ YAPI KİMYASALLARI SAN. ve TİC. LTD. ŞTİ. İstanbul Mermerciler Küçük San. Sit. 18. Cad. No: 22 Köşeler Köyü - Dilovası / KOCAELİ 18 DoP number: 03.PB 1504-2.003	
2163-CPR-0560-1 TS EN 1504-2 DSA DECORATIVE PLASTER PRIMER Products and systems for the protection and repair of concrete structures-Definitions, requirements, quality control and conformity assessment-Part 2: Surface protection systems for concrete Principle 1: Protection against foreign material, Method 1.2: Impregnation application	
Capillary water absorption and water permeability	: < 0,1 kg/m ² .h ^{0,5}
Processing depth	: Class I; <10 mm
Fire response class	: A1
Dangerous materials	: Suitable