



DECLARATION OF PERFORMANCE (NO: 03.PB 1504-2.009, 2163-CPR-0560-2)
EU Construction Products Directive Annex 3 (305/2011/EU)

1. Unique identification code of the product-type: **MYFIX N-34 Negative use waterproofing mortar**
2. Type, batch or serial number or any other elements allowing identification of the building material (in accordance with the fourth paragraph of Article 13 of the Regulation): Principle 2: Moisture Control (MC)
Method 2.2: Coating Application (C)
3. Intended use or uses of the building material, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: EN 1504-2:2005
4. The name of the manufacturer, registered trade name or trademark and contact address of the manufacturer (in accordance with the fifth paragraph of Article 13 of the Regulation): **YILDIZ YAPI KİMYASALLARI SAN. ve TİC. LTD. ŞTİ.**
İstanbul Mermerciler Küçük Sanayi Sitesi 18. Cad.
No:22 Dilovası / KOCAELİ / TURKEY
5. Where applicable, name and address of the authorised representative (whose mandate covers the task specified in the second paragraph of Article 14 of the Regulation): Not relevant
6. System or systems of assessment and verification of the stability of the performance of the building material (as specified in Annex-5 of the Regulation): System 2+
7. In a declaration of performance (DOP) for a building material covered by a harmonized standard: **UNIVERSAL CERTIFICATION and identification number 2163** are used for the evaluation and verification of the performance of the system under **the control of the factory production** under **System 2+** and **the continuous monitoring, measurement and evaluation of the initial inspection and the factory production control of the production facility, the performance consistency certificate, factory production conformity certificate/test.**
8. European Technical Assessment References: Not relevant
9. Declared performance:

Essential characteristics	Performance	Harmonised Technical Specifications
Water vapour permeability	Class I; $s_D < 5$ m	EN ISO 7783-1 EN ISO 7783-2
Capillary water absorption and water permeability	$W < 0.1 \text{ kg/m}^2 \cdot \text{h}^{0.5}$	EN 1062-3
Adhesion strength by pull-off	Without traffic load; $\geq 0.8 \text{ N/mm}^2$	EN 1542
Fire response class	A1 (Amount of organic matter $< 1\%$)	EN 13501-1

*Our products do not contain hazardous substances for health and the environment.

10. The building material described in the first and second paragraphs has the performance declared in paragraph 9 of this Annex. The entire liability for this performance statement belongs solely to the manufacturer as defined in the fourth paragraph of this Annex.

Signed on behalf of the manufacturer:

Uğur YILDIZ / General Manager

TURKEY / 23.11.2021