



DECLARATION OF PERFORMANCE (NO: 05.PB 12004.006, 070645-TSE-05/04)
EU Construction Products Directive Annex 3 (305/2011/EU)

1. Unique identification code of the product-type:	MYFIX GRANIFIX Ceramic and granite tile adhesive
2. Type, batch or serial number or any other elements allowing identification of the building material (in accordance with the fourth paragraph of Article 13 of the Regulation):	Cementitious (C) – High performance (2) - Reduced slip feature (T) - Extended open time (E) C2TE
3. Intended use or uses of the building material, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:	EN 12004:2017
4. The name of the manufacturer, registered trade name or trademark and contact address of the manufacturer (in accordance with the fifth paragraph of Article 13 of the Regulation):	YILDIZ YAPI KİMYASALLARI SAN. ve TİC. LTD. ŞTİ. İstanbul Mermerciler Küçük Sanayi Sitesi 18. Cad. No:22 Dilovası / KOCAELİ / TURKEY
5. Where applicable, name and address of the authorised representative (whose mandate covers the task specified in the second paragraph of Article 14 of the Regulation):	Not relevant
6. System or systems of assessment and verification of the stability of the performance of the building material (as specified in Annex-5 of the Regulation):	System 3
7. In a declaration of performance (DOP) for a building material covered by a harmonized standard: Organized by <u>TSE</u> by applying <u>manufacturer's factory production control</u> under <u>System 3</u> , one of the systems of evaluation and verification of performance invariance, <u>determination of material type based on type test of approved laboratory material, type calculations, values given in table or explanatory documents</u> .	
8. European Technical Assessment References:	Not relevant
9. Declared performance:	

Essential characteristics	Performance	Harmonised Technical Specifications
High initial tensile adhesion strength	$\geq 1.0 \text{ N/mm}^2$	EN 12004-2:2017 Article 8.3
High tensile adhesion strength after water cycle	$\geq 1.0 \text{ N/mm}^2$	EN 12004-2:2017 Article 8.3
High tensile adhesion strength after heat cycle	$\geq 1.0 \text{ N/mm}^2$	EN 12004-2:2017 Article 8.3
High tensile adhesion strength after freeze/thaw cycling	$\geq 1.0 \text{ N/mm}^2$	EN 12004-2:2017 Article 8.3
Extended Open Time: Tensile adhesion strength	After 30 minutes $\geq 0.5 \text{ N/mm}^2$	EN 12004-2:2017 Article 8.1
Slip	$\leq 0.5 \text{ mm}$	EN 12004-2:2017 Article 8.2
Fire response class	A1	EN 13501-1

*Our products do not contain hazardous substances for health and the environment.

10. The building material described in the first and second paragraphs has the performance declared in paragraph 9 of this Annex. The entire liability for this performance statement belongs solely to the manufacturer as defined in the fourth paragraph of this Annex.

Signed on behalf of the manufacturer:

Uğur YILDIZ / General Manager

TURKEY / 23.11.2021